



Revision: 1.0 - 01/17/2017  
Install Time: 20 Minutes

Installation should be performed by a trained technician. Use caution when installing this kit. Proper tools are necessary and you must have a bike lift to safely secure and raise the rear of the bike and suspension in order to install the parts. We recommend the use of a factory service manual.

**INCLUDED IN THE KIT:**

(2) 1/2-13 X 1.5" HEX HEAD GRADE 8 GOLD ZINC	(4) 1/2" FLAT WASHER GOLD ZINC
(2) 1/2-13 X 2.5 HEX HEAD GRADE 8 GOLD ZINC	LEFT & RIGHT LOWERING BLOCKS
(4) 1/2" SPLIT LOCK WASHER CLEAR ZINC	

**INSTRUCTIONS:**

- Begin by removing saddlebags and placing aside.
  - Place a stand or jack under the motorcycle frame. Make sure stand or jack is centered. Raise motorcycle slowly and check for stability. Raise until the weight is just off the rear tire.
  - Remove bottom bolts from stock shocks and tilt them back out of the way.
  - Install lowering blocks to swing arm using supplied 1/2-13 x 1.5" grade 8 bolts using red thread locker and supplied washer and lock washer.
  - Reinstall bottom shock bolts using supplied 1/2-13 x 2.5" grade 8 bolts using red thread locker and supplied washer and lock washer.
  - Check all hardware and re-install saddlebags.
  - Always remember to check critical hardware at normal service intervals.
- CAUTION:** Do not exceed motorcycle manufacturers suggested weight and load limits.
- WARNING:** Installing a lowering kit will decrease initial ground clearance. The motorcycle will be lower to the ground and care should be taken to avoid bottoming, especially over bumps or in turns. To maintain proper balanced geometry, the front and rear of the motorcycle should be lowered equally. Failure to properly install the lowering kit and operate the motorcycle after installation may result in serious injury or death to the rider.
- LIMITED GUARANTY:** Because we cannot control the application of our products, buyer assumes risks for any and all damage caused to him or herself or any third party by virtue of any failure of these parts. Guaranty for such parts is limited to our replacement costs thereof. This guaranty is in lieu of all other guaranties or warranties express or implied, and all other such guaranties or warranties are hereby expressly disclaimed. By installation of these parts, buyer irrevocably agrees to the foregoing.

Our install guides provide a basic outline on the proper installation of our products. Further tuning and/or fitment may be required. LA Choppers bears no responsibility on installation costs associated with this product.  
© 2019 LA Choppers